

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

U.S. PATENT APPLICATION

OF


KARI HILTUNEN

FOR

**TOUCH-SENSITIVE NAVIGATION SURFACES FOR MOBILE
TELECOMMUNICATION SYSTEMS**

I hereby certify that this document is being deposited with the United States Postal Service on this date, March 19, 2001, in an envelope marked as and with sufficient postage as "Express Mail - Post Office to Addressee," Mailing Label No. EL762607695US, addressed to the Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

Judith Schick



**TOUCH SENSITIVE NAVIGATION SURFACES FOR MOBILE
TELECOMMUNICATION SYSTEMS**

Technical Field

5 The present invention relates generally to touch sensitive surfaces and deals more particularly with providing a touch sensitive navigational surface as a user interface and more specifically for a communication device.

Background of the Invention

10 Communication devices such as for example, cellular phones and mobile radiophones typically have mechanical or contact switches for a keypad to dial a phone number or as function keys to access features or other capabilities of the communication device. Additionally, such devices typically have a carbon or electret microphone and a miniature voice coil or piezoelectric or other such type
15 speaker to convert audio signals to electrical signals or to convert electrical signals to audio, respectively. Likewise, separate switches such as roller switches or directional switches are typically provided to scroll a menu or selection functions, i.e. phone number lists, volume increase/decrease, ringing tones, and the like, presented on a display screen of the communication device. Although touch screen
20 technology can function as a user-interface by allowing a user to "touch" an area of the screen to choose a desired one of a number of preprogrammed possible selections, such technology is limited to display screens only.

 It would be desirable therefore to provide a communication device having "touch" sensitive surfaces that function as a sensor, microphone or speaker to
25 replace the various discrete individual components performing the corresponding functions in current communication devices and to enhance the operation of the device.

Summary of the Invention

An object of the invention is to provide a method and related apparatus for a new sensor system for communication devices using an electromechanical dielectric (EMD) film coextensive with at least a portion of the surface of the device.

- 5 A further object of the invention is to provide a touch sensitive navigational surface as a user interface for a communication device.

Another object of the invention is to provide a communication device in which any surface of the device can be made to act as sensor, microphone or speaker.

- 10 Yet another object of the invention is to provide a communication device wherein the sensors are integrated with the physical structural components of the communication device by injection molding.

- 15 Further objects of the invention will become apparent in the following specification wherein the detailed description is provided for purposes of disclosing the invention without placing limitations thereon.

- 20 In a first aspect of the invention, a method for providing a sensor system in a communication device is presented. The method includes the steps of: providing an electromechanical dielectric (EMD) film integral with the surface of the cover of the communication device; providing one or more open areas in the outer surface regions in the cover for accessing the EMD film wherein the open area corresponds to the operational function to be implemented; and coupling the EMD film in each of the exposed regions to electronic circuit means associated with the corresponding operational function of the communication device.

- 25 Preferably, the step of providing one or more voided or open areas in the outer surface region includes providing one or more open areas in the inner surface region of the cover in those areas where the EMD film requires unobstructed movement to perform the desired operational function of transforming an acoustic

signal to a corresponding electrical signal and transforming an electrical signal to a corresponding acoustic signal.

Preferably, the method further includes the step of providing a display in one of the voided areas with the rear surface of the display facing and in contact with the surface of the EMD film.

Preferably, the step of providing the EMD film integral with the surface of the cover includes the step of injection molding the cover with the EMD film.

In a second aspect of the invention, a communication device embodying the invention is presented. The communication device includes an electromechanical (EMD) film coextensive with at least a portion of the surface of the cover of the communication device; one or more voided or open areas in the outer surface regions in the cover for accessing a portion of the EMD film wherein a given voided area in the surface of the cover corresponds to the operational function to be implemented; electronic circuit means coupled to the EMD film for sensing electrical signals generated by the EMD film in response to a force applied to the surface and for displacing the surface of the EMD film with respect to a plane of the surface of the cover in response to electrical signals generated by the electronic circuit means.

Preferably, the EMD film functions as a speaker.

Preferably, the EMD film functions as a microphone.

Preferably, the EMD film functions as a keypad.

Preferably, the communication device further includes a display in contact with the EMD film whereby the EMD film is responsive to sensing the direction of touching on the surface of the display.

In a further aspect of the invention, a portable, handheld communication device of the type having means for establishing a communication link between itself and a remote communication device is presented and includes a case having at least a first portion molded from material responsive to displacement for generating an

electric signal, and at least a second portion molded from material responsive to electric signals for displacement of said material proportional to the magnitude of the electrical signal.

5 Preferably, the first portion and the second portion are molded from electromechanical dielectric (EMD) film, and the EMD film is coextensive with at least a portion of the surface of the case.

Preferably, the communication device further includes security means for controlling access limiting call completion to an authorized user.

10 Preferably, the security means includes at least a portion of the EMD film configured as a fingerprint recognition system.

In a yet further aspect of the invention, a method for providing touch-sensitive surface functionality in a conventional communication device is presented. The method includes the steps of: providing an electromechanical dielectric (EMD) film with a first major surface having adhesion properties; placing the first adhesion
15 major surface in contact with a desired location of a surface of the communication device; and coupling the EMD film to electronic circuit means associated with the corresponding operational function of the communication device.

Preferably, the method includes the steps of providing an EMD film with a second major surface disposed opposite the first major surface and having adhesion
20 properties and locating the EMD film between the cover of the device and a display screen of the device, whereby the EMD film holds the display in place to provide a touch-sensitive screen.

Preferably, the method further includes the steps of: providing an EMD film with a second major surface disposed opposite the first major surface; providing a
25 flexible protective layer on the second major surface; and attaching the adhesion major surface of the EMD film to a desired location on the surface of the device, whereby the protective layer faces outward for touching contact by a user.

In a still further aspect of the invention, a conventional communication device having touch-sensitive surface functionality is presented. The communication device includes an electromechanical dielectric (EMD) film with a first major surface having adhesion properties and a second major surface oppositely disposed the first major surface, whereby the adhesion major surface holds the EMD film in contact with a desired location on the surface of the communication device, and means for coupling the EMD film to electronic circuit means associated with the corresponding operational function of the communication device.

Preferably, the communication device further includes the EMD film second major surface having adhesion properties and a display in contact with and held by the EMD film second major surface.

Preferably, the communication device further includes the EMD film second major surface having a flexible protective layer.

Brief Description of the Drawings

Fig. 1 is a cross-sectional view of the structure of the electromechanical dielectric (EMD) film used with the present invention;

Fig. 2 is a representation of an electron microscope photo of a cross-section of the structure of the EMD film;

Fig.3 is a schematic representation of a cellular phone embodying the sensor system of the present invention;

Fig. 4 is a schematic cross sectional view of the EMD film supported for use as a sensor;

Fig. 5 is a schematic cross sectional view of the EMD film supported for use as a keypad;

Fig.6 is a schematic cross-sectional view of the EMD film and display for use as a touch sensitive screen;

Fig. 7 is a schematic cross section view of the EMD film supported for use as a microphone or a speaker;

Fig. 8 is a schematic representation of a cellular phone having security access embodying the sensor system of the present invention.

5

Detailed Description of Preferred Embodiments

Turning now to the drawings and considering the invention in further detail, an electromechanical dielectric (EMD) film is illustrated schematically in cross-sectional view in Fig. 1 and is generally designated 10. The EMD film 10 is a foil like and flexible polymer film with a permanent electric charge. When a mechanical or acoustic force is applied to the surface, the EMD film generates a voltage that can be detected. Therefore the EMD film functions as sensor in this configuration. The EMD film also works in the opposite direction that is, converting an applied electrical potential to displace the film relative to the plane of the surface. Therefore, the EMD film functions as an actuator in this configuration.

Still referring to Fig. 1, the EMD film 10 is made of a thin (about 0.50 μm) biaxial-oriented polypropylene 12. The biaxial orientation and special additives produce many small flat bubbles 14 in the material and these bubbles give the EMD film its properties. A permanent electric charge is injected into the EMD material during the manufacturing process. Thin metal electrodes 16, 18 are evaporated or laminated on both surfaces 20, 22 of the film to complete the EMD structure. Fig.2 shows a representation of an electron microscope photo of a cross section of the EMD film structure. Further details on the construction and principles of operation of the EMD film may be had from literature commonly available in the art and from US Patent No. 4,654,546 entitled, "Electromechanical Film and Procedure for Manufacturing Same." The electromechanical dielectric film such as that used in the present invention is available commercially under the trade name "EMFi™".

Turning now to Fig. 3, a schematic representation of a cellular phone embodying the sensor system of the present invention is illustrated therein and is generally designated 50. The cellular phone 50 is conventional in appearance in the illustration in Fig. 3 and includes a case 52 typically molded of a thermoplastic polymer material or other materials now known or future developed for use in such applications. An alphanumeric keypad 54 is provided as a user interface for example, for inputting phone numbers to be dialed, inputting alphanumeric characters into a memory for subsequent retrieval, accessing functions of the cellular phone and for other such operations typically well known to those in the cellular phone art. Additional keys or buttons 56 corresponding to additional features of the cellular phone may also be present. The microphone is located in the region designated 58 to receive and convert audio signals, such as speech, into corresponding electrical signals for use with the cellular phone. An earpiece is located in the region 60 to convert electrical signals received and processed in the cellular phone to audio signals such as speech for communicating with the user. A display generally designated 62, shows typical messages and graphics associated with cellular phone operation, such as the number dialed, menu functions, text messages, and other such graphics as is commonly known in the cellular telephone art. The EMD film must be solidly supported along one major face side when it is used as a sensor because it is so thin (approximately 50 μm), it would deflect and not respond to light touches or forces applied to its opposite unsupported side. Additionally, a sensor built from the EMD film would be extremely light and not add weight or bulk to a communication device. As will become more apparent below, the keypad, microphone, speaker and display functions can be implemented utilizing the EMD film with corresponding electrical circuitry of the cellular phone to perform the intended functions.

Fig. 4 is a schematic cross-sectional fragmentary view of the EMD film supported for use as a sensor in accordance with the present invention. In the

illustrated example, the EMD film generally designated 100, is shown supported by the surface 104 formed by the relief area 106 formed in the case or cover 102. A force such as a touching force applied in the direction 108 causes the outer surface 110 of the EMD film 100 to move slightly in the direction 108. The support surface 104 of the relief area 106 prevents flexing or movement of the bottom side 112 of the EMD film thus the film can be compressed or deformed when touched to generate a corresponding electrical signal. A thin flexible protective polymer layer 114 covers the surface 110 of the EMD film and the surface 116 of the cover 102. Although the relief support area is somewhat exaggerated in the figures for purposes of description, in actuality the EMD film is substantially thinner than the thickness of the cover and is readily integrated as part of the surface of the cover.

The EMD film can be electrically coupled to a resistive ladder network to provide increasing and decreasing in accordance with the direction of touching on the surface of the cover. Such a ladder network might be used for example as a volume control for the audio in the form of speech or in the form of ringing tones, response verification tones and the like. Another application could be to increase or decrease the illumination of a display screen keypad, or other selection key.

One method of manufacturing an integrated EMD film coextensive with the surface of a case or cover made from a plastic, polymer or other such material is to use a multi-component injection molding process. The injection molding process can be used to provide a touch-sensitive surface area of the cover. In the multi-component injection molding process, the first step is to injection mold the hard portion of the cover which provides the support surface for the EMD film in a sensor application. The next step is to place the EMD film into the mold in an orientation such that the EMD film is in contact with its support surface in the molded cover. Next, the outer surface portion of the case is molded using a soft elastomer or other hard polymer to cover the hard part of the cover and the EMD film to form an integral unit. Manufacturing the case in this manner provides a

continuous touch-sensitive surface that can be coupled to electrical circuitry within the phone as required.

Fig. 5 is a schematic cross-sectional view of the EMD film supported for use as a keypad and is similar to the illustration in Fig. 4. In Fig. 5, tactile domes 120 corresponding to each location of a key is placed on the surface 122 of the EMD film 124. The dome 120 provides tactile feedback to a user when the key is pushed. As can be seen from the illustration, the domes 120 contact the surface 122 of the EMD film 124 in the region 126 below the tactile dome, which force F applied by the dome 120 in the direction of arrow 128 causes an electrical signal to be generated by the EMD film. The region of the EMD film beneath the dome 120 is coupled to electronic circuit means that detect the electrical signal when the key is pressed and transforms the signal to the proper information corresponding to the key pushed by the user. In the multi-component injection molding process, the EMD film and the domes are inserted into the mold in contact with the support area in an orientation so that the back of the EMD film is against the support surface and the domes face outward. The final stage of the injection molding covers the surface and domes with a soft elastomer or other hard polymer to form an integral unit of the keypad and cover. Domes providing tactile feedback are well known to those skilled in the art. The domes may be of any known or future developed type to achieve the intended function. The domes may further be carried by a protective polymer sheet or may be overlaid by a protective flexible laminate well known to those in the keypad art. Alternately, the final stage of injection molding may include applying the proper alphanumeric indicia to the corresponding locations of the covering elastomer or polymer.

In alternate embodiments, the EMD film can be configured as the desired functional component, that is, a keypad, microphone, speaker, touch sensor, and the like, in the electronic device without injection molding.

Turning now to Fig. 6, a schematic cross-sectional view of a touch sensitive screen for use in a communication device is illustrated therein and generally designated 200. The case 202 has a support surface 204 formed by the relief area 206 sized and shaped in the cover to mount a typical display 208 used with a cellular phone. The display 208 is generally held in place by means of adhesive tape between the bottom side 210 of the display and the surface 204 of the relief area 206. In the embodiment shown in Fig. 6, the EMD film 212 has its oppositely disposed surfaces 214 and 216, respectively, modified to provide high adhesion between the surface 204 of the relief area 206 of the cover and the back surface 218 of the display screen 208. A glue or other adhesive suitable for use with the polymer or other material of the cover and the display is selected to provide maximum adhesion between the EMD film surface 216 and the surface 204 and the back surface 218 of the display so that all movements along the surface 220 of the display 208 are transferred to and sensed by the EMD film 212. A thin flexible protective polymer layer 222 may overlay the surface 220 of the display 208 and the surface 224 of the cover 202. Construction of a touch sensitive screen in this manner has high reliability because dirt, water and other harmful substances cannot enter behind and interfere with the operation of the display screen 208.

Turning now to Fig. 7, a schematic cross-sectional view of the EMD film supported for use as a microphone or speaker is illustrated therein and generally designated 250. The cover 252, is open or voided, that is, there is an absence of material forming the cover in the areas 254, 256 disposed oppositely on the outer side 258 and inner side 260 of the cover 252. The outer side 258 is the surface portion of the cover molded from a soft elastomer or other hard polymer as described above. The EMD film 262 is supported along its peripheral edges 264 to allow the EMD film 262 to deflect or vibrate back and forth in a direction indicated by the arrow 266. The EMD film 262 functions as a microphone and generates an electrical signal having a magnitude and frequency corresponding to the acoustic

energy impinging on the surface 268 of the EMD film 262. The electrical signal is coupled from the metal electrodes on the surfaces of the EMD film to electronic circuitry via electrical conductors, printed circuit paths or other conductive means known to those skilled in the electrical arts. In a similar way, the EMD film 262
5 can function as a speaker and deflect or vibrate back and forth displacing air in contact with the surface of the EMD film to produce acoustic energy having a magnitude and frequency corresponding to an electrical signal coupled to the EMD film from the electronic circuitry of the phone. A thin flexible protective polymer layer 270 may overlay the surface 268 of the EMD film and the surface 258 of the
10 cover 252. The polymer layer 270 must be of sufficient flexibility to not dampen the movement of the EMD film. Alternately, the outer surface of the EMD film can be covered with a decorative material.

Turning now to Fig. 8, a schematic representation of a cellular phone having security access embodying the sensor system of the invention is shown therein and is
15 substantially similar to the cellular phone described in Fig. 3 and is generally designated 300. The cellular phone 300 includes a fingerprint identification and verification platen 302. The control circuitry of the cellular phone can be programmed or configured to require placement of the finger of an authorized user to the platen 302 to gain initial access to the phone or to complete a call. The EMD
20 film must be supported as described above for use as a sensor and a very thin polymer layer is used on the surface of the EMD film to achieve maximum sensitivity of the surface of the EMD film and to minimize any potential affect on accuracy of the fingerprint recognition system. Fingerprints can be characterized by selecting a minimum number of indicia points corresponding to loops and ridges as
25 well known to those in the fingerprint recognition art. In the present illustration, the user will initially place their finger on the platen in accordance with prompts shown on the cellular phone display. The fingerprint recognition system "learns" the fingerprint in this step and stores it in a memory means as an image or other

format for subsequent retrieval and comparison during the call access or completion operations. One or more users can be authorized to access and complete calls with the phone. Since the number of potential users is limited, the recognition process and matching time interval is very short and not inconvenient for a user. Additional
5 safeguards can be employed such as a password used with the fingerprint recognition system.

The display screens of currently known communications devices can also be made to have touch-sensitive screen capability and functionality. In this instance, the EMD film surfaces are suitably made to have adhesion properties similar to the
10 adhesive tape used to hold the current displays in place in the communication device. The so-modified EMD film is substituted for the adhesive tape in the current devices to provide the touch-sensitive screen capability and functionality without modifying or changing the conventional construction and cover. Obviously, the electronics of the communication device are changed to accommodate connection
15 to and operational functionality with the EMD film.

Likewise, any surface of currently known communication devices can be made to have touch-sensitive capability and functionality without modifying or changing the conventional construction and cover of the device. In this instance, the EMD film has a protective flexible layer on one surface and an adhesive layer on its
20 opposite surface to allow the EMD film to be adhesively attached to a surface of the device. The adhesive surface could be self-sticking and have a releasable cover over the adhesive. Again, the electronics of the communication device would be changed to accommodate connection to and operational functionality with the EMD film.

A touch sensitive navigational surface for a communication device has been
25 described above in several preferred embodiments. It will be recognized by those skilled in the art that numerous changes and modifications may be made without departing from the spirit and scope of the invention. For example, the surface of the cover may be made from different materials and not limited to materials that are

suitable for injection molding processes only. Therefore the invention has been disclosed by way of illustration and not limitation.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2